



FAST RECOVER RECTIFIER

FR501 THRU FR507

VOLTAGE RANGE
CURRENT


50 to 1000 Volts
5.0Ampere

FEATURES

- Low coat construction
- Fast switching for high efficiency.
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed:
260°C/10 secods/.375"(9.5mm)lead length at 5 lbs(2.3kg) tension

MECHANICAL DATA

- Case: Transfer molded plastic
- Epoxy: UL94V-O rate flame retardant
- Polarity: Color band denotes cathode end
- Lead: Plated axial lead, solderable per MIL-STD-202E method 208C
- Mounting position: Any
- Weight: 0.042ounce, 1.19 grams



DO-27

Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

- Ratings at 25°C ambient temperature unless otherwise specified
- Single Phase, half wave, 60Hz, resistive or inductive load
- For capacitive load derate current by 20%

	SYMBOLS	FR 501	FR 502	FR 503	FR 504	FR 505	FR 506	FR 507	UNITS
Maximum Repetitive Peak Reverse Voltage	V _{RRM}	50	100	200	400	600	800	1000	Volts
Maximum RMS Voltage	V _{RMS}	35	70	140	280	420	560	700	Volts
Maximum DC Blocking Voltage	V _{DC}	50	100	200	400	600	800	1000	Volts
Maximum Average Forward Rectified Current 0.375"(9.5mm) lead length at T _A = 75℃	I _(AV)	5.0							Amp
Peak Forward Surge Current 8.3mS single half sine wave superimposed on rated load (JEDEC method)	I _{FSM}	300							Amps
Maximum Instantaneous Forward Voltage @ 3.0A		V _F	1.3						Volts
Maximum DC Reverse Current at Rated DC Blocking Voltage	T _A = 25℃	I _R	10						μA
	T _A = 100℃		500						
Maximum Reverse Recovery Time (Note 3) T _J =25℃		trr	150			250	500		ns
Typical Junction Capacitance (Note 1)		C _J	60						pF
Typical Thermal Resistance (Note 2)		R _{θJA}	20						℃/W
Operating Junction Temperature Range		T _J	(-65 to +150)						℃
Storage Temperature Range		T _{STG}	(-65 to +150)						℃

Notes:

- 1.Measured at 1.0MHz and Applied Reverse Voltage of 4.0Volts.
- 2 Thermal Resistance from junction to Ambient at .375"(9.5mm)lead length, P.C.board mounted.
- 3.Reverse Recovery Test Conditions: $I_F = 0.5\text{mA}$, $I_R = 1.0\text{mA}$, $t_{rr} = 0.25\text{A}$



FAST RECOVER RECTIFIER

FR501 THRU FR507

VOLTAGE RANGE
CURRENT

50 to 1000 Volts
5.0Ampere

RATING AND CHARACTERISTIC CURVES FR501 THRU FR507








FIG.6-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC

